

IT 1002

IT 2002









- All-rounder for construction sites and workshops (IP 23)
- Precise results through advanced inverter technology

- Energy Package for larger studs, used on construction sites and workshops

M3 to M16 (type RD)
#4 to 5/8" (type RD)

M3 to M24
#4 to 1"



Welding process	ARC, SC	ARC, SC
Welding material	  	  
Technology	Inverter	Inverter
Equipment		
Welding with ceramic ferrule	X	X
Welding with shielding gas	X	X
Process control	(optional)	--
Automation	(optional)	--
4 gun/head connections	--	--
Display	Digital	Digital
Welding range	M3 to M16 (type RD), dia. 2 to 14 mm / #4 to 5/8" (type RD), dia. 14 ga to 9/16"	M3 to M24, dia. 2 to 22 mm / #4 to 1", dia. 14 ga to 1"
Welding rate	M12 / 1/2" = 25 studs/min	Dia. 22 / 7/8" = 6 studs/min
Welding current	1000 A (max.)	2000 A (max.)
Current adjustment range	100 to 1000 A, electrode 50 to 400 A (stepless)	300 to 2000 A (stepless)
Welding time	5 to 1000 ms (stepless)	5 to 1500 ms (stepless)
Primary power	400 V*, 3 phases, 50/60 Hz, 35 AT	400 V*, 3 phases, 50/60 Hz, 63 AT
	*alternative primary power see „Order No.“	*alternative primary power see „Order No.“
Primary plug	32 A (with 400 V mains)	63 A (with 400 V mains)
Connected load	50 kVA (with 400 V mains)	100 kVA (with 400 V mains)
Cooling type	F (temperature controlled cooling fan)	F (temperature controlled cooling fan)
IP Code	IP 23	IP 23
Dimension LxWxH (without handle)	660 x 280 x 340 mm /	600 x 500 x 830 mm /
Weight	31 kg	95 kg
Suitable guns	A 12, A 12-FL, A 16, CA 08	A 12, A 12-FL, A 16, A 22

Order No.

93-60-1202 (400 V)
93-66-1202 (480/460 V)

Order No.

93-60-2202 (Gas, 400 V)
93-66-2202 (Gas, 480/460 V)



93-40-020 (Ground cable, 5 m, 25 mm², 2 vice grips 10")

93-40-019 (Ground cable, 2 pcs., 5 m, 70 mm², 1 vice grip 10")

Legend Welding process: ARC = Drawn arc stud welding, SC = Short cycle stud welding

 Mild steel  Stainless steel  Aluminium